

3

DATA SHEET AND PERFORMANCE

AUGERS Mod. CR150 / CR154

GUIDELINES		U.o.M.							
OIL CAPACITY	lt/min	10	20	25	30	35	40	50*	
OIL PRESSURE	bar	80							
RPM	rpm	180	370	490	580	680	780	990	
		VOLUMETRIC CAPACITY							
		m ³ /h							
WORKING ANGLE	0°	14,9	27,5	36,4	43,0	50,4	57,9	73,4	
	30°	11,8	21,7	28,7	34,0	39,8	45,7	58,0	
	45°	10,2	18,8	24,9	29,5	34,6	39,6	50,3	
	60°	8,6	15,9	21,1	25,0	29,3	33,6	42,6	
	90°	5,5	10,2	13,4	15,9	18,7	21,4	27,2	

COCLEE Mod. CR200 / CR204

GUIDELINES		U.o.M.							
OIL CAPACITY	lt/min	10	20	30	40	50	60	70*	
OIL PRESSURE	bar	80							
RPM	rpm	110	240	370	500	620	750	870	
		VOLUMETRIC CAPACITY							
		m ³ /h							
WORKING ANGLE	0°	24,18	49,01	75,56	102,11	126,62	153,17	178	
	30°	19,1	38,7	59,7	80,7	100	121	140	
	45°	16,6	33,6	51,8	69,9	86,7	104,9	122	
	60°	14	28,4	43,8	59,2	73,4	88,8	103	
	90°	8,9	18,1	28	37,8	46,8	56,7	65,7	

*: for intermittent use only